

DH series: a mixed customization of signal, power and data; connectors from M20 to M24, from 2 cores to 24 cores  
 USB, RJ45 and water-proof optical fibre are available for choice.

series \ Multi-Core	2PIN	3PIN	4PIN	5PIN	6PIN	7PIN	8PIN	9PIN	10PIN	12PIN	19PIN	24PIN	Installation size
DH24													<p>USB RJ45 Optical</p>
Working pressure	500v		500v		500v		500v		500v		500v		
1 minute for AC. V	2500v		2500v		2500v		2500v		2500v		2500v		
Rated current	20A		20A		20A		20A		20A		20A		
DH20													
Working pressure	500v	500v	500v	500v	400v	400v	400v	250v	250v	250v	250v	250v	250v
1 minute for AC. V	2500v	2500v	2500v	2500v	2000v	2000v	2000v	1500v	1500v	1500v	1500v	1500v	1500v
Rated current	20A	20A	20A	20A	12A	12A	12A	5A	5A	5A	5A	5A	5A

The whole series of DH: Durance  $\geq 500$  times; work temperature ranging from  $-40^{\circ}\text{C}$  to  $80^{\circ}\text{C}$ ; hardware: aluminium alloy  
 pin: copper alloy | gilt gold; water-proof gasket: silica gel ; Flame retardancy rating: UL94-V0; exterior cover: metal, plastic, metal + plastic;  
 insulation components: high-performance engineering plastic